

# BIG EASY® Composite Frac Plug

## Key Benefits and Features

- Short, fully-composite assembly allows for quick drill-out and minimal debris
- Composite upper and lower slips prevent slippage in hardened casing
- Composite shoe prevents flow-blockage when flowing back well
- Slip design, angled elements, and cone profiles minimize the risk of swabbing and premature setting
- Bottom profile prevents plug-on-plug spinning during drill-out



Use in the following applications:

Land

The Frank's International BIG EASY® Frac Plug is a fully-composite plug for use as a temporary barrier to separate zones during fracturing or stimulation operations. The BIG EASY® is available with drop- ball or caged-ball configurations and is rated up to 10,000 psi at 300°F.

## Specifications

Casing Size (IN.)	Weight (LBS/FT)	Casing ID Range (IN.)	OD (IN.)	Slip Insert Type	Pressure Rating (PSI)	Maximum Temperature (°F)	Length (IN.)	Setting Tool
4-1/2"	11.6 - 13.5	3.920 - 4.000	3.66	CERAMIC	10,000	200	21.25	#10
				MCC	10,000	300	19.5	
5-1/2"	17.0 - 23.0	4.670 - 4.892	4.38	CERAMIC	10,000	200	19.5	#20
				CERAMIC	8,000	250	17.6	

\*Operational temperature range can be adjusted based on elastomeric material compound.