

Well Construction

Frank's Tubular Running Service (TRS) - Drilling Services

Mega Elevator - Combination Casing and Drill Pipe Elevator

Features and benefits

- Door-type design equipped with bail rotator, to pick-up casing/drill pipe horizontally from cart/conveyor or vertically from racked-back stand
- Ability to switch from running casing to landing string with only minor adjustments and without swapping components
- While dressed for 6 5/8-inch drill pipe, the 14-inch Mega Elevator's EXTENDED RANGE[™] capabilities enable running 7 5/8-inch – 14-inch casing strings without slip changes or tool adjustments
- While dressed for 6 5/8-inch drill pipe, the 11 7/8-inch Mega Elevator's EXTENDED RANGE™ capabilities enable running 7 7/8-inch – 11 7/8-inch casing strings without slip changes or tool adjustments



Specifications

Specifications			
	14-inch Mega Elevator	11 7/8-inch Mega Elevator	
Casing size range (in.)	6 1/2 - 14	6 1/2 - 11 7/8	
Drill pipe sizes (in.)	5 1/2, 5 7/8, 6 5/8 (45° or 18°)	5 1/2, 5 7/8, 6 5/8 (45° or 18°)	
Capacity	750 Tons	750 Tons	
Bails	750 / 500 Ton	750 / 500 Ton	
Operation type	Hydraulic	Hydraulic	
Width (in.)	73 3/4	67 1/2	
Length (in.)	45 3/8	49	
Height (in.)	30	36 5/8	
Weight (lbs)	14,00	10,68	



exprogroup.com/frankstrs

Date 03/2025 | Revision 2.0

Copyright 2025 Expro. All Rights Reserved. Notice: this product is protected by one or more patents assigned to Expro or one of its affiliated entities. For more information regarding Expro's patents, please go to: www. expro.com/patents. The sale, rental and use of Expro's products and the offering of services are subject to Expro's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Expro. Product and service information and/or specifications are subject to change without notice. For more information, please contact an authorized Expro representative.