



CX-Enviroplug

Confidently setting an environmental barrier for P&A operations has traditionally been limited to complex and costly mechanical bridge plugs and inflatable devices.

The CX-Enviroplug is a cementing plug used to provide a reliable base for cement in larger ID casing, which removes the complexity and restraints associated with other environmental barriers. The CX-Enviroplug is run with a Coretrax disconnect sub, allowing cementing operations to take place once the plug has been released.

Made from fully drillable materials, the tool contains a one-way valve and bypass ports which prevents surging when running in hole. The three-finned design also features a weight set element that allows for pressure testing of the plug.



BENEFITS

- Suitable for a range of applications with sizes up to 30" available
- Compression set elastomer with pressure testing of up to 1,000 psi
- Open-ended cement stinger allowing for cementing to take place in same run in hole



SPECIFICATIONS

Casing Size	Casing Weight	Max OD (Fins)	Max Hard OD	Compression Set Element	Upper Connection	Max Test Rating
18 ⁵ / ₈ "	87.5#	19.50"	17.25"	Yes	3 ¹ / ₂ " EUE Box	1,000 psi
20"	94#	19.50"	17.25"	Yes	3 ¹ / ₂ " EUE Box	500 psi
26"		26.3"	24"	No*	4 ¹ / ₂ " EUE Box	N/A
30"	310#	29.80"	25.875"	No*	4 ¹ / ₂ " EUE Box	500 psi

*available with brush

Other sizes available on request.