

CX-Riser Brush



The Coretrax Riser Brush is an integral part of the drill string and is designed to clean the riser as the pipe is run into and pulled out of the well. It is stabilized slightly below the drift diameter of the riser to centralise the drill string.

The strong, flexible bristles provide the necessary force and contact to effectively remove residual drilling fluid, scale and other foreign materials from the ID of the riser to ensure a clean surface.

The one-piece tool can be rotated or reciprocated without fear of damage to the riser or the tool. It can be run with the clean-up string and remain in the riser during the clean-up circulation and may be short tripped in the well at the beginning or at the end of the clean-up operation. It has no internal seal elements.

BENEFITS

- Available in a range of sizes to suit a variety of operations
- Brushes provide 360° coverage
- High fluid bypass to allow debris to flow past and between brush assemblies
- Compatible with the entire Coretrax Wellbore Clean-up Tool line
- Solid robust casing brush element eliminating any potential damage to brushing element and debris build up and damage to tool body

APPLICATIONS

- Wellbore clean-up
- Drilling
- Completion



SPECIFICATIONS

Dimensional Data	21″ Tool	24″ Tool
Brush OD	20.25"	22.81"
Carrier OD	18.400"	21.00"
Body ID	3.000"	3.000"
Fishing Neck Length	24.25"	24.25"
Fishing Neck OD	6.650"	6.650"
Retainer Sleeve OD	9.000"	9.000"
TFA Under Brush Sleeves (sq.in)	39.27"	39.27"

Tool Connection Specifications			
Rig Connection Type	NC50	NC50	
Torsional Yield Strength (lbs.ft)	44,200	44,200	
Max. Recommended Make-up Torque (lbs.ft)	27,000	27,000	
Tensile Strength (lbs)	944,000	944,000	

Other sizes available on request.

