



# CX-Enviroplug



## Confidently setting an environmental barrier for P&A operations has traditionally been limited to complex and costly mechanical bridge plugs and inflatable devices.

The CX-Enviroplug is a cementing plug used to provide a reliable base for cement in larger ID casing, which removes the complexity and restraints associated with other environmental barriers. The CX-Enviroplug is run with a Coretrax disconnect sub, allowing cementing operations to take place once the plug has been released.

Made from drillable materials, the tool contains a one-way valve and bypass ports which prevents surging when running in hole.

The three-finned design also features an optional weight set element that allows for pressure testing of the plug.

### BENEFITS

- Suitable for a range of applications with sizes up to 30" available
- Compression set elastomer with pressure testing of up to 500 psi
- Open-ended cement stinger allowing for cementing to take place in same run-in hole



## SPECIFICATIONS FOR CX-ENVIROPLUG WITH COMPRESSION SET ELEMENT

Casing Size	Casing Weight	Max OD (Fins)	Max Hard OD	Brush Accessory Available	Upper Connection	Max Test Rating
18 5/8"	87.5#	19"	17.25"	on request	3 1/2" EUE Box	500 psi
20"	94#	19"	17.25"	on request	3 1/2" EUE Box	500 psi

## SPECIFICATIONS FOR BASIC CX-ENVIROPLUG

Casing Size	Casing Weight	Max OD (Fins)	Max Hard OD	Brush Accessory Available	Upper Connection
18 5/8"	87.5#	19.69"	17.0"	on request	3 1/2" EUE Box
20"	94#	19.69"	17.0"	on request	3 1/2" EUE Box
26"		26.3"	24"	Yes	4 1/2" EUE Box
30"	310#	29.80"	25.625" (w/brush 25.875")	Yes	4 1/2" EUE Box

Other sizes available on request.