



CX-Tubing Hanger



The Coretrax Tubing Hanger is pipe deployed and compression set, lending itself to several applications including hanging sacrificial tubing during P&A operations. This can deliver significant rig time savings and reduce costs and risks associated with tubular handling and disposal.

The robust slips allow for the tubing hanger to be set in open hole and cased hole where scale may be present. The Coretrax Tubing Hanger is easily set and can be adapted to act as a base for cement.

BENEFITS

- Easily Set
- Can be used with a various tubing connections
- Can be adapted to act as a base for cement
- Available in a range of sizes from 4" to 13-3/8"



SPECIFICATIONS

Casing		Recommended Hole Size	Gauge OD	Differential Pressure
Size	Weight			
3 1/2"	5.7-10.2#	2.867"-3.258"	2.75"	10,000 psi
4"	5.6-14.0#	3.340"-3.732"	3.12"	10,000 psi
4 1/2"	9.5-16.6#	3.826"-4.090"	3.50"	10,000 psi
5"	11.5-18.0#	3.920"-4.560"	3.71"	10,000 psi
5 1/2"	13.0-25.0#	4.580"-5.047"	4.24"	10,000 psi
5 3/4"	22.5-25.2#	4.580"-5.047"	4.24"	10,000 psi
6"	14.0-26.0#	5.140"-5.595"	4.75"	10,000 psi
7"	17.0-35.0#	5.989"-6.655"	5.61"	10,000 psi
	23.0-40.0#	5.595"-6.366"	5.34"	10,000 psi
7 5/8"	20.0-39.0#	6.625"-7.263"	6.09"	10,000 psi
8 5/8"	24.0-49.0#	7.511"-8.248"	6.96"	10,000 psi
9 5/8"	29.3-53.5#	8.435"-9.063"	7.71"	8,000 psi
10 3/4"	54.0-81.0#	9.250"-9.784"	8.71"	8,000 psi
	32.7-51.0#	9.850"-11.150"	9.50"	5,000 psi
11 3/4"	38.0-60.0#	9.850"-11.150"	9.50"	5,000 psi
13 3/8"	48.0-72.0#	12.347"-12.715"	12.00"	3,000 psi
	77.0-102.0#	11.633"-12.464"	11.56"	3,000 psi
16"	65.0-109.0#	14.688"-15.250"	14.25"	2,000 psi
18 5/8"	76.0-96.5#	17.655"-18.730"	17.25"	2,000 psi
20"	133.0-169.0#	17.655"-18.730"	17.25"	2,000 psi

Casing OD	Casing Weight	Gauge OD	Setting Range	Maximum Differential Pressure (Above Only)	Minimum Hang Weight	Maximum Hang Weight
7"	17# - 26#	6.000"	6.276" - 6.538"	4,000 psi	14,000 lbs	140,500 lbs
7"	17# - 38#	5.750"	5.920" - 6.538"	4,000 psi	14,000 lbs	133,000 lbs
7"	20# - 29#	5.969"	6.184" - 6.456"	4,000 psi	14,000 lbs	140,500 lbs
7 5/8"	33.7# - 39#	6.453"	6.625" - 6.765"	4,000 psi	16,000 lbs	160,000 lbs
8 5/8"	24# - 36#	7.656"	7.825" - 8.097"	4,000 psi	14,000 lbs	100,000 lbs
8 5/8"	24# - 40#	7.500"	7.725" - 8.097"	4,000 psi	14,000 lbs	100,000 lbs
9 5/8"	32.3# - 43.5#	8.500"	8.755" - 9.001"	3,000 psi	20,000 lbs	250,000 lbs
9 5/8"	43.5# - 53.5#	8.250"	8.535" - 8.755"	3,000 psi	20,000 lbs	250,000 lbs
10 3/4"	32.3# - 55.5#	9.500"	9.760" - 10.192"	5,000 psi	10,000 lbs	445,000 lbs
11 3/4"	42# - 65#	10.500"	10.682" - 11.084"	3,000 psi	10,000 lbs	211,500 lbs
13 3/8"	48# - 77#	12.000"	12.275" - 12.715"	3,000 psi	27,000 lbs	250,000 lbs