

## **Well Construction**

## Frank's Tubular Running Service (TRS) - Casing Technologies

## Wide Track Remote Tong System (RTS)

Expro's Wide Track RTS is a modular system capable of making up and breaking out a large range of pipe sizes with three different tong cassette modules. The self-contained system supports Expro's 7 5/8 inch Casing and Tubing Tong Cassette, Expro's 14 3/8 inch Casing Tong Cassette, and Expro's XT-22 Casing Tong Cassette. The Wide Track System is designed to operate in two configurations: one which utilizes its own rail system that can be installed on top of the rig floor and one which uses the rig's built in iron roughneck rails.

## **Features and Benefits**

- · 2 rail options:
  - Expro's supplied rail system
  - · Rig's iron roughneck rails
- Modular cassette system
  - · Cassettes can be installed into carriage in minutes
- Self-contained air over hydraulic control operates independently from rig's control systems
- Hydraulic supply options:
  - Portable diesel units
  - Portable electric units
  - Rig-supplied hydraulics
- Compatible with Expro's Data Trek® Torque Turn Monitoring System
- Compatible with Expro's Integrated Control System for torque hold required connections
- 14 3/8 in Cassette provides for variable separation distance between tong and backup to accommodate casing and drill pipe landing string connections
- 7 5/8 in Cassette can be supplied with Expro's Fluid Grip™ for the ultimate in non-marking gripping systems for use on CRA tubulars



Specifications				
	Wide Track Carriage*	X-22 Tong Cassette Module	14 3/8 Tong Cassette Module	7 5/8 Tong Cassette Module
Overall dimensions (I x w x h)	110 in x 86 in x 110 in	105 in x 63 in x 96 in	90 in x 54 in x 90 in	90 in x 54 in x 90 in
Cassette weight	13,000 lbs w/ XT-22 Cassette	8,500 lbs	6,700 lbs	3,900 pounds
Torque high gear	N/A	18,000 ft-lbs	11,000 ft-lbs	5,600 ft-lbs
Torque low gear	N/A	100,000 ft-lbs	70,000 ft-lbs	30,000 ft-lbs
Maximum speed	N/A	19 1/4 rpm	34.6 rpm	60 rpm
Casing size range	N/A	9 5/8 in - 22 in	4 5/8 in - 14 3/8 in	2 in - 7 5/8 in
Vertical Stroke	50 in			Optional Fluid Grip™ kit available

<sup>\*</sup>Accepts 3 Expro's Tong Cassettes, Emergency Shut Down Features



expro.com/frankstrs

Date 04/2024 | Revision 1.0