

Well Construction

Downhole Service Tools

BRUTE® Halo Anchor Sub

The BRUTE® Halo is a modular anchor sub integrated into the field proven BRUTE® Packer System, eliminating the need for tailpipe during well suspension operations. It transforms the BRUTE® Packer System into an all-in-one solution capable of handling various packer applications.

Features and Benefits

- Eliminates the requirement for tailpipe during well suspension operations
- Modular anchor sub works seamlessly with the BRUTE® Packer System for “plug-n-play” integration
- Enables the BRUTE® Packer System to become an all-in-one packer system that enhances operational flexibility and versatility in packer applications
- Anchor Sub is API 11D1 qualified, keeping to the full operating envelope of the rest of the system

Applications

- Weather emergencies and storm suspensions
- Temporary suspensions including:
 - Wellhead repair
 - BOP testing
 - Riser disconnects
 - Batch drilling/suspension operations



Specifications

Casing Size	Max Tool OD (in)	Minimum Casing ID (in)	Maximum Casing ID (in)	Minimum Set Down Weight (lbs)	Required Torque (ft/lbs)	Pressure Rating (psi)	Temperature Rating (F°)	Secondary Release Overpull (lbs)
9-3/8" – 10-7/8"	8.250	8.363	9.673	60,000	5,000	10,000 (above) / 7,500 (below)	40-250	115,200