

Well Construction

Frank's Tubular Running Service (TRS) - Casing Technologies

21 in. Casing Tong

Features and benefits

- Hydraulic shift
- Optional integral back-up
- Equipped with Expro's proprietary safety door interlock system
- Capable of torque measurements with Frank's DATA TREK[®]
- Advantage torque turn monitoring system and/or hydraulic load cell
- Can be used with Expro's Tong Pusher Arm (TPA)



Specifications						
	High Gear RPM/Torque	Low Gear RPM/Torque	Handle Length	Weight	Size Range	Additional Features
21" Casing Tong	64 rpm @ 6,000 ft-lb	7.5 rpm @ 79,000 ft-lb	52"	4,900lbs (2,223kg) tong only 6,300lbs (2,858kg) with backup	9 5/8" - 21"	1,2,4

Additional Features:

- 1) Hydraulic Shift
- 2) Optimized Camming System
- 3) Standard Integral Back-Up

4) Optional Integral Back-Up



exprogroup.com/frankstrs

Date 10/2024 | Revision 2.0

Copyright 2024 Expro. All Rights Reserved. Notice: this product is protected by one or more patents assigned to Expro or one of its affiliated entities. For more information regarding Expro's patents, please go to: www.expro.com/patents. The sale, rental and use of Expro's products and the offering of services are subject to Expro's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Expro. Product and service information and/or specifications are subject to change without notice. For more information, please contact an authorized Expro representative.