

Well Construction

Frank's Tubular Running Services (TRS) - Casing Technologies

Scissor Lift Tong Positioning System

Features and benefits

- Unique tong positioning system allows safe manipulation of power tongs to and from well center without the use of tugger or cables
- Remote control capabilities allow for hands-off operations
- Built-in patented slippage sensor safety feature
 Can be used as a stand-alone carriage system or driven by
- Can be used as a stand-alone can age system of driven by an AR-5000 Iron Roughneck
 Compatible with Expro's 30 in and 36 in tongs with integral
- Compatible with Exprois 30 in and 36 in tongs with integral zero-side load hydraulic backups



Specifications	
Safe working load	14,200 lbs [6,441 kg] (36 in tong with integral HBT)
Shipping dimensions (LxWxH)	95 x 84 x 49 in [2,413 x 2,134 x 1,245 mm]
Shipping weight	10,250 lbs [4,649 kg] with motor drive assembly (to be used as carriage)
Elevation travel	26 in [660 mm]



expro.com/frankstrs

Date 12/2024 | Revision 1.0

Copyright 2024 Expro. All Rights Reserved. Notice: this product is protected by one or more patents assigned to Expro or one of its affiliated entities. For more information regarding Expro's patents, please go to: www.expro.com/patents. The sale, rental and use of Expro's products and the offering of services are subject to Expro's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Expro. Product and service information and/or specifications are subject to change without notice. For more information, please contact an authorized Expro representative.