

Hydraulic Catwalk THS-11





Key Benefits and Features

- Safely increases pipe handling speeds between the pipe-rack and rig floor by eliminating crane hazards
- Dramatically reduces the risk of accidents through explosion-proof, remote operations
- Programmable Logic Controller (PLC) system controls automation and functionality through sensors to reduce maintenance, replacement parts, and down time
- Reduces footprint and logistics requirements by fitting onto one truck for ease of mobility
- Foldable pipe loaders enable ability to fit onto most rigs without need to modify configurations or remove existing catwalk
- Protects chrome tubulars with UHMW PE-1000 polyeurethane applied layer across machine pathways
- Advanced telescoping system positions pipe closer to the well bore to ease pick-up and laydown rig floor operations

Use in the following applications:

Shelf

Land

Specifications

Equipment Type	Mechanized - Electromechanical and Hydraulic	Max Pressure	3600 psi [250 bar]
Machine Total Weight	50,700 pounds [23.0 tons]	Max Flow Rate	44.6 GPM (169 L/min) @ 2250 rpm
Machine Total Length	76 - 93.8 feet [23.2 - 28.6 meters]	Pipe Weight	8,800 pounds [4.0 tons]
Rig Floor Height	10 - 42 feet [3 - 12.8 meters]	Pipe Length	Up to 50 feet [15 meters]
Electrical Motor	No.2 x 22 kW @50 Hz / 25 kW @60 Hz	Pipe OD Max	30 inches
Hydraulic Pump	No.2 Variable Displacement	Time for Cycle	Less than 120 seconds
Voltage	380-480 V	Controls	Radio Remote, Cable Remote, Manual & HMI Touchscreen Display
Frequency	50-60 Hz	Pipe Type	HWDC, HWDP, DP, CSG, TBG, CRA/Chrome
Transport Loads	No. 1		
Transport Dimensions	43.0 x 8.2 x 9.8 ft (13.1 x 2.5 x 3.0 meters)		

franksinternational.com

For more information call 1-800-833-7265

©2021 Frank's International. All Rights Reserved. Notice: this product is protected by one or more patents. For more information regarding Frank's International's patents, please go to: www.franksinternational.com/patents/. Frank's International products and services are subject to the Company's standard terms and conditions, available on request. Unless noted otherwise, trademarks and service marks herein are the property of Frank's International. Product and service information and/or specifications are subject to change without notice. For more information please contact an authorized Frank's International representative.