

Safety Joint and Overshot (SFJT)

The Safety Joint provides for an emergency release between the work string and the packer. In the event that the Safety Joint is released, the Overshot can be run to reconnect the work string with the packer assembly.

Specifications:

Working pressure	15,000 psi/103.42 Mpa
Working temperature (See note 1)	350°F/175°C
OD (in/mm)	5" / 127mm
ID (in/mm)	2.25"/57.2mm
Upper thread connection	3 ½" IF
Lower thread connection	3 ½" IF
Tensile strength	350,000lbf/155,600daN
Tensile strength at max working pressure	30,000lbf/13.345daN
Tool length (in/mm)	27.2in/690.88mm
Tool weight (lbs/kg)	140 lbs/ 63.6 kg
Service condition	H2S per Nace MR-01-75

Note 1: Working temperature can be increased by changing sealing configuration as follows:
Up to 400°F/204°C – Standard elastomers and premium back-up rings.

Releasing operation:

The Safety Joint is run on the test string directly above the packer. Release is effected by taking an upstrain on the test string and rotating to the right. Release is controlled by make-up torque, which can be varied. Eleven turns are required to back off the Safety Joint.

Retrieving operation:

The Safety Joint can be reconnected to the test string by slowly setting down and rotating the overshot to the right into the retrieving threads.

