

# Well Construction

## Frank's Tubular Running Services (TRS)

### Landing String Equipment - Elevators

#### Features and Benefits

- Both the 1,250 and 1,500 Ton Drill Pipe Elevators were the industry's first 1,250 and 1,500 ton handling equipment
- Equipped with Expro's elevator/spider interlock system
- No latches or doors, eliminating pinch points
- Manufactured out of wrought materials (no castings)
- Can be supplied with bushings to run drill pipe with 18° or 45° upset angle



#### Specifications

Model	Weight (lbs)	Length (in.)	Height (in.)	Width (in.)	Pipe size range
1,250 Ton	6,880	47	33 1/2	53	4 1/2 - 7 5/8
1,500 Ton	8,010	53	38	47	4 1/2 - 7 5/8

# Well Construction

## Frank's Tubular Running Services (TRS)

### Landing String Equipment - Spiders

#### Features and Benefits

- The SBS 1000 has a 1,000 ton load rating
- Both the SBS 1250 and SBS 1500 were the industry's first 1,250 and 1,500 ton load rating
- The SBS 1000 and SBS 1250 will fit into most 37 1/2 inch rotary tables without the use of adapter rings
- The SBS 1500 will fit into most 49 1/2 inch rotary tables without the use of adapter rings
- Equipped with Expro's elevator/spider interlock system
- Slips boast an increased slip crush capacity over other slips currently on the market
- Manufactured out of wrought materials (no castings)
- For use in deepwater and ultra-deepwater applications



#### Specifications

Model	Weight (lbs)	Length (in.)	Height (in.)	Width (in.)	Height above rotary (in.)	Pipe size range (in.)
1,000 Ton Split Bushing Spider (SBS)	5,468	38 5/8	29 1/4	39 3/8	5 7/8	4 1/2 - 7 5/8
1,250 Ton Landing String Split Bushing Spider	7,880	38 5/8	33	38 3/4	15 3/4	4 1/2 - 7 5/8
1,500 Ton Landing String Split Bushing Spider	13,050	57	36	52 3/8	15 7/8	4 1/2 - 7 5/8