

Well Construction

Frank's Tubular Running Service (TRS) - Completions Technologies

750-ton Hydraulic Control Line Spider (HCLS750)

Features and benefits

- EXTENDED RANGE™ capabilities allow tool to run tapered tubing strings with only minor adjustments and without changing slips
- Equipped with Expro's unique spider/elevator Interlock system, which ensures the spider/elevator is properly set on the pipe before the companion tool is allowed to open
- Up to a 15-inch pass through diameter that provides the ability to pass large OD control line or umbilical clamps through the tool body
- Options for control line/umbilical protection including Rotating Control Line Guard (RCLG), Cantilever COBRA™, and Control Line Pusher Arm
- Able to accept up to 4-inch umbilical with RCLG and 5 1/2-inch umbilical with the Cantilever COBRA™ and Control Line Pusher Arm
- Top cover rated to 100 tons

Specifications

Size range (in. / cm)	4 1/2 - 9 5/8 (12 - 24)
Capacity (tons / tonnes)	750 (680)
Rotary size (in./mm)	37 1/2 (95)
Max. width (in./mm)	48 (122)
Height (in./mm)	54 (137)
Height (above floor) (in./mm)	29 1/4 (74)
Weight (lbs/kg)	9,100 (4,128)
Operation type	Hydraulic

